



Foundry Hook KWB, GH/S Grade 10 - Eye

Product information

Foundry Hooks are hooks with a bigger opening without safety latch often used in foundries.

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 380°C

Finish: Violet powder coated.

Standard: EN 818-4

Note: Always verify if hooks without safety latch are allowed for your application.

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | EWL mm | For chain ø mm | a mm | b mm | d1 mm | d2 mm | e mm | g mm | h mm | Weight kg |
|--------------|------------|---------|--------|----------------|------|------|-------|-------|------|------|------|-----------|
| 402300250320 | GH/S-7/8 | 2.5 | 131 | 7-8 | 25 | 118 | 24 | 11 | 131 | 64 | 29 | 0.94 |
| 402300400320 | GH/S-10 | 4 | 158 | 10 | 32 | 143 | 31 | 14 | 158 | 76 | 35 | 1.62 |
| 402300670320 | GH/S-13 | 6.7 | 190 | 13 | 40 | 170 | 39 | 17 | 190 | 89 | 42 | 3.24 |
| 402301000320 | GH/S-16 | 10 | 224 | 16 | 46 | 200 | 47 | 22 | 224 | 102 | 50 | 5.65 |
| 402301600320 | GH/S-19/20 | 16 | 260 | 19 | 54 | 231 | 56 | 28 | 260 | 114 | 61 | 9.5 |

Blueprint

