



## Load Hook HKS/S Grade 10 - Clevis/Latch

### Product information

Clevis Load hook - Sling hook with safety latch for general lifting applications.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 380°C

**Finish:** Violet powder coated.

**Standard:** EN 1677-2

(+ 25% WLL)

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	EWL mm	For chain ø mm	e mm	h mm	a mm	d mm	g mm	b mm	Weight kg
402300140430	HKS/S-6	1.4	69	6	69	20	15	7	19	66	0.25
402300190430	HKS/S-7	1.9	95	7	95	28	19	9	26	90	0.68
402300250430	HKS/S-8	2.5	95	8	95	28	19	10	26	90	0.58
402300400430	HKS/S-10	4	109	10	109	35	25	12.5	31	108	1.14
402300670430	HKS/S-13	6.7	136	13	136	41	34	16	39	131	2.02
402301000430	HKS/S-16	10	155	16	155	49	37	20	45	153	3.57
402301600430	HKS/S-19/20	16	184	19-20	184	53	51	24	53	177	5.55
402301900430	HKS/S-22	19	214	22	214	62	52	27	62	196	8.99

Blueprint

