

Master Link Assemblies G/S Grade 10



Product information

Master link sub-assembly.

Material: Alloy steel

Marking: Code and grade.

Finish: Violet powder coated.

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

| Part Code | Code | Chain diameter | WLL ton | Chain mm | d mm | d1 mm | e mm | t mm | t1 mm | s mm | w mm | w1 mm | Weight kg |
|--------------|-----------|----------------|---------|----------|------|-------|------|------|-------|------|------|-------|-----------|
| 402100420250 | G/S-6 | - | 4.2 | 6 | 19 | 13 | 189 | 135 | 54 | 10 | 75 | 25 | 1.28 |
| 402100760250 | G/S-7/8 | - | 7.6 | 7+8 | 23 | 17 | 230 | 160 | 70 | 14 | 90 | 34 | 2.37 |
| 402100960250 | G/S-10 | - | 9.6 | 10 | 27 | 20 | 265 | 180 | 85 | 14 | 100 | 40 | 3.75 |
| 402101400250 | G/S-13 | - | 14 | 13 | 33 | 23 | 315 | 200 | 115 | 17 | 110 | 50 | 6.6 |
| 402102120250 | G/S-16 | - | 21.2 | 16 | 36 | 27 | 400 | 260 | 140 | 20 | 140 | 65 | 10.06 |
| 402103410250 | G/S-19/20 | 6 | 34.1 | 19 | 50 | 33 | 500 | 350 | 150 | 26 | 190 | 70 | 22.87 |
| 402104000250 | G/S-22 | - | 40 | 22 | 50 | 36 | 520 | 350 | 170 | - | 190 | 75 | 24.79 |
| 402105600250 | G/S-26 | - | 56 | 26 | 56 | 45 | 570 | 400 | 170 | - | 200 | 80 | 37.6 |

Blueprint

