



Safety Hook HSB/S

Product information

Safety hook with Eye.

Material: Alloy steel

Marking: According to standard, code and grade

Finish: Violet powder coated.

Standard: EN 1677-3

(+ 25% WLL)

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | EWL mm | a mm | b mm | d1 mm | d2 mm | e mm | g mm | h mm | S max | Weight kg |
|--------------|----------------|---------|--------|------|------|-------|-------|------|------|------|-------|-----------|
| 402300140400 | HSB/S-6-10 | 1.4 | 110 | 17 | 71 | 21 | 11 | 110 | 28 | 20 | 1 | 0.52 |
| 402300250400 | HSB/S-7/8-10 | 2.5 | 136 | 20 | 88 | 25 | 12 | 136 | 34 | 26 | 1 | 0.92 |
| 402300400400 | HSB/S-10-10 | 4 | 169 | 29 | 107 | 35 | 17 | 169 | 45 | 30 | 1 | 1.57 |
| 402300670400 | HSB/S-13-10 | 6.7 | 205 | 35 | 138 | 40 | 20 | 205 | 52 | 40 | 1.5 | 3.19 |
| 402301000400 | HSB/S-16-10 | 10 | 251 | 41 | 168 | 50 | 27 | 251 | 60 | 50 | 2 | 6.24 |
| 402301600400 | HSB/S-19/20-10 | 16 | 290 | 50 | 194 | 60 | 30 | 290 | 70 | 62 | 2 | 9.75 |
| 402301900400 | HSB/S-22-10 | 19 | 322 | 52 | 211 | 70 | 32 | 322 | 81 | 65 | 2 | 11.45 |

Blueprint

