



## Safety Hook HSB/S

### Product information

Safety hook with Eye.

**Material:** Alloy steel

**Marking:** According to standard, code and grade

**Finish:** Violet powder coated.

**Standard:** EN 1677-3

(+ 25% WLL)

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | Code           | WLL ton | EWL mm | a mm | b mm | d1 mm | d2 mm | e mm | g mm | h mm | S max | Weight kg |
|--------------|----------------|---------|--------|------|------|-------|-------|------|------|------|-------|-----------|
| 402300140400 | HSB/S-6-10     | 1.4     | 110    | 17   | 71   | 21    | 11    | 110  | 28   | 20   | 1     | 0.52      |
| 402300250400 | HSB/S-7/8-10   | 2.5     | 136    | 20   | 88   | 25    | 12    | 136  | 34   | 26   | 1     | 0.92      |
| 402300400400 | HSB/S-10-10    | 4       | 169    | 29   | 107  | 35    | 17    | 169  | 45   | 30   | 1     | 1.57      |
| 402300670400 | HSB/S-13-10    | 6.7     | 205    | 35   | 138  | 40    | 20    | 205  | 52   | 40   | 1.5   | 3.19      |
| 402301000400 | HSB/S-16-10    | 10      | 251    | 41   | 168  | 50    | 27    | 251  | 60   | 50   | 2     | 6.24      |
| 402301600400 | HSB/S-19/20-10 | 16      | 290    | 50   | 194  | 60    | 30    | 290  | 70   | 62   | 2     | 9.75      |
| 402301900400 | HSB/S-22-10    | 19      | 322    | 52   | 211  | 70    | 32    | 322  | 81   | 65   | 2     | 11.45     |

# Blueprint

