

Geared Trolley TSG KITO



Product information

General: Geared trolley with capacity from 0,125 tons up to 5 tons. The standard trolley includes rubber bumper, safety lug and suspender.

Material: Pressed steel plate.

Marking: According to standard, CE-marked

Temperature range: -40°C up to +60°C (-20°C up to + 40°C for the use with a electric chain hoist)

Standard: EN 13157

Safety factor: 4:1

Part Code	WLL ton	Beam width mm	Model	Chain length m
502600013050030	0.125	164-305	W30	3
502600011630030	0.125	58-163	Standard	3
502600031630030	0.25	58-163	Standard	3
502600033050030	0.25	164-305	W30	3
502600053050030	0.5	164-305	W30	3
502600051630030	0.5	58-163	Standard	3
502600103050030	1	164-305	W30	3
502600101630030	1	58-163	Standard	3

502600153050030	1.5	205-305	W30	3
502600152040030	1.5	82-204	Standard	3
502600203050030	2	205-305	W30	3
502600202040030	2	82-204	Standard	3
502600253050030	2.5	205-305	W30	3
502600252040030	2.5	82-204	Standard	3
502600303050030	3	205-305	W30	3
502600302040030	3	82-204	Standard	3
502600503050030	5	205-305	W30	3.5
502600502040030	5	100-204	Standard	3.5
502600753050030	7.5	221-305	W30	3.5
502600752200030	7.5	150-220	Standard	3.5
502601003050030	10	221-305	W30	4.0
502601002200030	10	150-220	Standard	4
502601503050030	15	221-305	W30	4.5
502601502200030	15	150-220	Standard	4.5
502602003050030	20	221-305	W30	4.5
502602002200030	20	150-220	Standard	4.5
502603001900030	30	190	Standard	4.5