

Lifting Eye RUD VWBG-V



Product information

- Rotating 360°, pivoting 230°
- Optical markings for easy determination for withdraw from service
- Ball bearing

Marking: According to standard

Standard: EN 1677-1

Safety factor: 4:1

| Part Code | WLL | A mm | B mm | C mm | D mm | E mm | F mm | G mm | M mm | T mm | Weight |
|-------------|------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------|
| 42157103720 | 0.3 | 8 | 31 | 29 | 30 | 27 | 13 | 36 | M8 | 76 | 0.18 |
| 42157103715 | 0.45 | 8 | 31 | 29 | 33.5 | 30 | 17 | 38 | M10 | 78 | 0.29 |
| 42157100180 | 0.6 | 10 | 49 | 35 | 42 | 36 | 21 | 47 | M12 | 107 | 0.44 |
| 42157100800 | 2 | 13 | 54 | 35 | 62 | 55 | 33 | 67 | M20 | 137 | 1.42 |
| 42157100640 | 3.5 | 18 | 66 | 40 | 81 | 70 | 40 | 88 | M24 | 173 | 2.63 |
| 42157100650 | 5 | 22 | 90 | 50 | 99 | 85 | 50 | 106 | M30 | 221 | 5.09 |

Blueprint

