

Container Hook POWERTEX CH

Product information



POWERTEX Container Hook CH for bottom lifting of containers is available in a Left (L), Right (R) and Straight (S) version. This product is part of the Powertex G10 Lifting Sling Chain Components range. It's an easy-to-use and cost-effective component for lifting containers.

- The container hooks in Left and Right version shall be used with a spreader beam with four inclined legs (two Left and two Right) at 45°+- 15°.
- The container hook Straight version shall be used with a spreader frame with four vertical legs 0° +- 15°.

To hooks must be used with 20 mm chain, and have a WLL of 16t.

Powerdex G10 Range benefits:

- 25% higher capacity compared to traditional Grade 8 components
- All POWERTEX G10 components are powder painted in luminous red
- Multi-functional master links and components are included in the range to allow quick and cost-effective assembly of chain slings
- The components meet EN 1677 part 1/2/3/4 +25% WLL
- Each forged component is crack detection tested, and samples are proof load tested.
- Each component is type tested in the factory and fatigue rated to 20,000 cycles at 1.5 times the WLL
- Full traceability through a batch number
- Replacement spare parts available
- All components are chromium 6 free
- POWERTEX 2.2 certificate enclosed with each box of components
- The components may also be used with Grade 8 chain to EN 818-2. In such a case, the chain sling needs to be rated as Grade 8 in accordance with EN 818-4.

Marking: According to standard, POWERTEX + Model (CH-20-10x) + traceability code.

Temperature range: -40 up to +200°C without reduction in WLL

Finish: Powder painted in luminous red

Standard: AS 3776

Standard: EN 1677-1

(+ 25% WLL)

Safety factor: 4:1

Grade: 10

| Part Code | Code | Chain diameter mm | WLL ton | MBL ton | EWL mm | Model | Packing Qty. | A mm | E mm | H mm | h mm | L mm | M mm | R mm | Ø1 | Ø2 | Weight kg |
|--------------|-----------|-------------------|---------|---------|--------|----------|--------------|------|------|------|------|------|------|------|----|----|-----------|
| 402301601490 | CH-20-10L | 20 | 16 | 64 | 190 | Left | 4 | 46 | 48 | 166 | 25 | 265 | 75 | 60 | 70 | 25 | 4 |
| 402301601510 | CH-20-10S | 20 | 16 | 64 | 190 | Straight | 4 | 46 | 48 | 166 | 25 | 265 | 75 | 60 | 70 | 25 | 4 |
| 402301601500 | CH-20-10R | 20 | 16 | 64 | 190 | Right | 4 | 46 | 48 | 166 | 25 | 265 | 75 | 60 | 70 | 25 | 4 |

Blueprint

