

## Lifting Eye Nut RUD RM, UNC thread



### Product information

- considerably higher WLL in comparison to DIN 582
- clear marking of the minimum WLL
- comprehensive range of threads

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Standard:** EN 1677-1

**Safety factor:** 4:1

| Part Code    | WLL ton | Thread Inch | A mm | B mm | C mm | D mm | E mm | T mm | Weight kg |
|--------------|---------|-------------|------|------|------|------|------|------|-----------|
| 421100020710 | 0.2     | 3/8 -16     | 12   | 11   | 10   | 25   | 25   | 34   | 0.1       |
| 421100040710 | 0.35    | 1/2 -13     | 14   | 13   | 12   | 30   | 30   | 41   | 0.17      |
| 421100080710 | 0.75    | 5/8 -11     | 16   | 15   | 14   | 35   | 35   | 48   | 0.26      |
| 421100120710 | 1.2     | 3/4 -10     | 18   | 17   | 16   | 40   | 40   | 55   | 0.39      |
| 421100150710 | 1.5     | 7/8 -9      | 22   | 21   | 20   | 50   | 50   | 70   | 0.7       |
| 421100200710 | 2       | 1 -8        | 28   | 26   | 24   | 60   | 60   | 85   | 1.4       |
| 421100300710 | 3       | 1 1/4 -7    | 28   | 26   | 24   | 60   | 60   | 85   | 1.35      |

# Blueprint

