



## Lifting Eye RUD VRS-F Starpoint, UNC thread

### Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

**Marking:** CE-marked

**Safety factor:** 4:1

| Part Code    | WLL<br>ton | Thread<br>Inch | B<br>mm | C<br>mm | D<br>mm | E<br>mm | G<br>mm | I<br>mm | K<br>mm | L<br>mm | N<br>mm | T<br>mm | Weight<br>kg |
|--------------|------------|----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 421100040740 | 0.4        | 3/8 -16        | 11      | 9       | 25      | 25      | 30      | 16.3    | 47      | 15      | 6.35    | 35      | 0.12         |
| 421100040745 | 0.4        | 7/16 -14       | 11      | 9       | 25      | 25      | 30      | 16.3    | 47      | 15      | 6.35    | 35      | 0.12         |
| 421100080740 | 0.75       | 1/2 -13        | 13      | 10      | 30      | 30      | 34      | 19.8    | 56      | 19      | 7.94    | 42      | 0.22         |
| 421100150740 | 1.5        | 5/8 -11        | 15      | 13      | 35      | 36      | 40      | 23.5    | 65      | 24      | 9.53    | 49      | 0.33         |
| 421100230740 | 2.3        | 3/4 -10        | 17      | 16      | 40      | 41      | 50      | 29.3    | 76      | 29      | 12.7    | 58      | 0.58         |
| 421100230745 | 2.3        | 7/8 -9         | 17      | 16      | 40      | 41      | 50      | 29.3    | 76      | 33      | 12.7    | 58      | 0.61         |
| 421100320740 | 3.2        | 1 -8           | 20      | 19      | 49      | 51      | 60      | 35      | 92      | 36      | 14.29   | 70      | 0.98         |
| 421100450740 | 4.5        | 1 1/4 -7       | 26      | 24      | 60      | 66      | 75      | 44      | 114     | 48      | 15.88   | 87      | 2.08         |
| 421100700740 | 7          | 1 1/2 -6       | 32      | 29      | 73      | 76      | 98      | 53      | 135     | 54      | 22.23   | 104     | 3.6          |
| 421100900740 | 9          | 1 3/4 -5       | 37      | 33      | 84      | 86      | 111     | 62      | 158     | 63      | 25.4    | 121     | 4.95         |
| 421101200740 | 12         | 2 -4.5         | 42      | 42      | 94      | 100     | 128     | 70      | 180     | 72      | 28.58   | 138     | 7.6          |

# Blueprint

