



Lifting Eye RUD VRS-F Starpoint, UNC thread

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

Marking: CE-marked

Safety factor: 4:1

| Part Code | WLL ton | Thread Inch | B mm | C mm | D mm | E mm | G mm | I mm | K mm | L mm | N mm | T mm | Weight kg |
|--------------|------------|----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 421100040740 | 0.4 | 3/8 -16 | 11 | 9 | 25 | 25 | 30 | 16.3 | 47 | 15 | 6.35 | 35 | 0.12 |
| 421100040745 | 0.4 | 7/16 -14 | 11 | 9 | 25 | 25 | 30 | 16.3 | 47 | 15 | 6.35 | 35 | 0.12 |
| 421100080740 | 0.75 | 1/2 -13 | 13 | 10 | 30 | 30 | 34 | 19.8 | 56 | 19 | 7.94 | 42 | 0.22 |
| 421100150740 | 1.5 | 5/8 -11 | 15 | 13 | 35 | 36 | 40 | 23.5 | 65 | 24 | 9.53 | 49 | 0.33 |
| 421100230740 | 2.3 | 3/4 -10 | 17 | 16 | 40 | 41 | 50 | 29.3 | 76 | 29 | 12.7 | 58 | 0.58 |
| 421100230745 | 2.3 | 7/8 -9 | 17 | 16 | 40 | 41 | 50 | 29.3 | 76 | 33 | 12.7 | 58 | 0.61 |
| 421100320740 | 3.2 | 1 -8 | 20 | 19 | 49 | 51 | 60 | 35 | 92 | 36 | 14.29 | 70 | 0.98 |
| 421100450740 | 4.5 | 1 1/4 -7 | 26 | 24 | 60 | 66 | 75 | 44 | 114 | 48 | 15.88 | 87 | 2.08 |
| 421100700740 | 7 | 1 1/2 -6 | 32 | 29 | 73 | 76 | 98 | 53 | 135 | 54 | 22.23 | 104 | 3.6 |
| 421100900740 | 9 | 1 3/4 -5 | 37 | 33 | 84 | 86 | 111 | 62 | 158 | 63 | 25.4 | 121 | 4.95 |
| 421101200740 | 12 | 2 -4.5 | 42 | 42 | 94 | 100 | 128 | 70 | 180 | 72 | 28.58 | 138 | 7.6 |

Blueprint

