



## Lifting Eye RUD VWBG-V - with variable length

### Product information

- Rotating 360°, pivoting 230°
- Optical markings for easy determination for withdraw from service
- Ball bearing

**Temperature range:** -40°C up to 100°C

**Safety factor:** 4:1

**Grade:** 10

<b>Part Code</b>	<b>WLL ton</b>	<b>A mm</b>	<b>B mm</b>	<b>C mm</b>	<b>D mm</b>	<b>E mm</b>	<b>F mm</b>	<b>G mm</b>	<b>M mm</b>	<b>T mm</b>
42158600331	0.45	8	31	29	33.5	30	10-122	38	M10	78
42158600332	0.6	10	49	35	42	36	12-140	47	M12	107
42158600337	1	13	46	38	48	41	14-160	56	M14	114
42158600333	1.3	13	46	38	48	41	16-180	56	M16	114
42158600338	1.8	13	54	35	62	55	18-83	67	M18	137
42158600334	2	13	54	35	62	55	20-223	67	M20	137
42158600334	2	13	54	35	62	55	22-94	67	M22	137
42158600335	3.5	18	66	40	81	70	24-255	88	M24	173
42158600335	3.5	18	66	40	81	70	27-92	88	M27	173
42158600336	5	22	90	50	99	85	30-330	106	M30	221

# Blueprint

