

Lifting Eye Starpoint RUD VRM



Product information

Design: Octagonal lifting eye.

For bolts with min. quality class 10.9

Material: Forged of high strength steel.

Marking: According to standard, CE-marked, WLL, indication for the most unfavourable case.

Finish: Striking fluorescent pink powder coating.

Standard: EN 1677-1

Safety factor: 4:1

| Part Code | Code | Diameter mm | WLL ton | Thread | WLL straight lift ton | B mm | C mm | D mm | E mm | F mm | G mm | H mm | I mm | K mm | L mm | N mm | T mm | Weight kg |
|--------------|------|-------------|---------|--------|-----------------------|------|------|------|------|------|------|------|------|------|------|------|------|-----------|
| 421100010272 | VRM | - | 0.1 | M6 | - | 9 | 7 | 20 | 23 | 16 | 28 | 17 | 13 | 37 | 11 | 9 | 28 | 0.06 |
| 421100030270 | VRM | 25 | 0.3 | M8 | 1 | 11 | 9 | 25 | 25 | 21 | 30 | 21 | 16.3 | 47 | 14 | 12 | 35 | 0.1 |
| 421100040270 | VRM | 25 | 0.4 | M10 | 1 | 11 | 9 | 25 | 25 | 21 | 30 | 21 | 16.3 | 47 | 14 | 12 | 35 | 0.1 |
| 421107500270 | VRM | 30 | 0.75 | M12 | 2 | 13 | 10 | 30 | 30 | 24 | 34 | 25 | 19.8 | 56 | 17 | 14 | 42 | 0.18 |
| 421100150270 | VRM | 35 | 1.5 | M16 | 4 | 15 | 13 | 35 | 36 | 30 | 40 | 29 | 23.6 | 65 | 21 | 19 | 49 | 0.32 |
| 421100230270 | VRM | 40 | 2.3 | M20 | 6 | 17 | 16 | 40 | 41 | 37 | 50 | 35 | 29.3 | 76 | 23 | 24 | 58 | 0.48 |
| 421100320270 | VRM | 48 | 3.2 | M24 | 8 | 20 | 19 | 49 | 51 | 45 | 60 | 41 | 35.2 | 92 | 29 | 30 | 70 | 0.83 |
| 421100450270 | VRM | 60 | 4.5 | M30 | 12 | 26 | 24 | 60 | 66 | 56 | 75 | 51 | 44 | 114 | 36 | 36 | 87 | 1.32 |

Blueprint

