



Lifting Eye Starpoint RUD VRS

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly available, look type VRS-F

Safety factor: 4:1

Part Code	WLL ton	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	M mm	N mm	T mm	Weight kg
421100031270	0.3	11	9	25	25	30	16.3	47	12	M8	6	35	0.11
421100041270	0.4	11	9	25	25	30	16.3	47	15	M10	6	35	0.11
421100081270	0.75	13	10	30	30	34	19.8	56	18	M12	8	42	0.19
421100081275	0.75	13	10	30	30	30	34	19.8	56	18	M14	8	0.2
421100151270	1.5	15	13	35	36	40	23.5	65	24	M16	10	49	0.32
421100231270	2.3	17	16	40	41	50	29.3	76	30	M20	12	58	0.54
421100321270	3.2	20	19	49	51	60	35	92	36	M24	14	70	0.86
421100451270	4.5	26	24	60	66	75	44	114	45	M30	17	87	1.5
421100701270	7	32	29	73	76	98	53	135	54	M36	22	104	3.3

Technical data

Working load limit in metric tons

RUD Load table VRS, VRS-F

Blueprint

