



## Lifting Eye VLBG-Z RUD, UNC with variable length

### Product information

- Captive but exchangeable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads

**Temperature range:** -40°C up to +100°C

**Safety factor:** 4:1

| Part Code    | WLL ton | Thread Inch | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm   | I mm | K mm | L mm    | N mm | T mm |
|--------------|---------|-------------|------|------|------|------|------|------|------|--------|------|------|---------|------|------|
| 421100061180 | 0.63    | 3/8 -16     | 30   | 54   | 34   | 24   | 39   | 10   | 29   | 10-98  | 75   | 45   | 39-127  | 32   | 75   |
| 421100101180 | 1       | 1/2 -13     | 32   | 54   | 34   | 26   | 38   | 10   | 29   | 13-123 | 75   | 45   | 42-152  | 32   | 75   |
| 421100151180 | 1.5     | 5/8 -11     | 33   | 56   | 36   | 30   | 39   | 13.5 | 36   | 16-148 | 86   | 47   | 52-184  | 38   | 85   |
| 421100251180 | 2.5     | 3/4 -10     | 50   | 82   | 54   | 45   | 55   | 16.5 | 43   | 19-185 | 113  | 64   | 62-228  | 48   | 110  |
| 421100251185 | 2.5     | 7/8 -9      | 50   | 82   | 54   | 45   | 55   | 16.5 | 43   | 22-211 | 113  | 64   | 65-254  | 48   | 110  |
| 421100401180 | 4       | 1 -8        | 50   | 82   | 54   | 45   | 67   | 18   | 43   | 25-211 | 130  | 78   | 68-254  | 48   | 125  |
| 421100501180 | 5       | 1 1/4 -7    | 60   | 103  | 65   | 60   | 64   | 22.5 | 61   | 32-278 | 151  | 80   | 93-339  | 67   | 147  |
| 421100801180 | 8       | 1 1/2 -6    | 77   | 122  | 82   | 70   | 97   | 26.5 | 77   | 38-270 | 205  | 110  | 115-347 | 87   | 197  |
| 421102001180 | 20      | 2 -4.5      | 95   | 156  | 100  | 95   | 105  | 36   | 87   | 51-302 | 230  | 130  | 138-389 | 100  | 222  |

## Blueprint

