



## Endurance 50DB

### Product information



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope  
Flexibility is optimised by the unique strand and rope construction.  
Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

**Standard:** EN 12385-4

**ISO 4309 Rope Category No:** All Diameters **RCN.23-1**

**Features:** Very High Breaking Load

**Material:** High Carbon Steel

**Marking:** On Termination ID and CE mark

**Finish:** Galvanised as standard

**Fill factor:** 0.64

**RCN:** 23-1

<b>Part Code</b>	<b>Rope Diameter, mm</b>	<b>Tensile strength N/mm<sup>2</sup></b>	<b>Min. Breaking force kN.</b>	<b>Finish</b>	<b>Weight kg/100m</b>
102100806270139	8	1,960	-	Galvanized	-
102100906270139	9	1,960	-	Galvanized	-
102101006270139	10	1,960	-	Galvanized	-
102101106270139	11	1,960	-	Galvanized	-
102101206270139	12	1,960	-	Galvanized	-
102101306270139	13	1,960	-	Galvanized	-
102101406270139	14	1,960	-	Galvanized	-
102101506270139	15	1,960	-	Galvanized	-
102101606270139	16	1,960	-	Galvanized	-
102101706270139	17	1,960	-	Galvanized	-
102101806270139	18	1,960	-	Galvanized	-
102101906270139	19	1,960	-	Galvanized	-
102102006270139	20	1,960	-	Galvanized	-
102102106270139	21	1,960	-	Galvanized	-
102102206270139	22	1,960	-	Galvanized	-