



## Wire Rope Clip with Forged Bridge POWERTEX PCTB

### Product information



The Powertex Wire Rope Clip with Forged Bridge PCTB is suitable for suspending static loads and single-use lifting operations. Available in sizes from 6 to 40 mm, this wire rope clip is designed and tested in accordance with the EN 13411-5B standard, ensuring compliance and reliability in every use.

#### Product benefits

- **Safety compliance:** These wire rope clips comply with EN 13411-5(Type B) standards, meeting stringent safety and quality requirements.
- **Superb grip:** The bridge features distinctive friction ridges that increase friction between the bridge and the wire rope, ensuring a secure grip where the rope makes contact with the bridge.
- **High load capacity:** When correctly mounted, the assembly can withstand up to 80% of the rope's minimum breaking load (MBL), providing robust and reliable performance.
- **Compatibility:** Designed for use with six-stranded right-hand lay ropes in 6x19 (M) and 6x36 classes and right-hand ordinary lay wire rope in 8x19 class up to 1960 N/mm<sup>2</sup>, with fiber core and steel core.
- **Durable finish:** 7-10 mm Dacromet, >10 mm are hot-dip galvanized
- **Full traceability:** Every Wire Rope Clip is marked with Powertex or PX branding, Size, and a traceability code, ensuring traceability to the production lot and raw materials.

**Material:** Carbon steel

**Marking:** Powertex (PX), Size, Batch no/traceability code

**Finish:** Dacromet or Hot-dip galvanized

**Warning:** Not suitable for use with compacted, hammered, or plastic-covered steel wire ropes. Additionally, these clips should not be used with spiral strand ropes.

## Blueprint

