

Ferrule UM Talurit®

Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for single layer steel wire ropes with round strands up to fill factor 0,60 and grade 1960.

Material: Aluminum

Marking: According to standard

Standard: EN 13411-3

except rope type range

Note: See the manufacturer's product data sheet below for guidance on dimension selection.

| Part Code | Ferrule size mm mm | Length mm |
|--------------|--------------------------|--------------|
| 120100900120 | 9 | 36 |
| 120101000120 | 10 | 41 |
| 120101100120 | 11 | 45 |
| 120101200120 | 12 | 50 |
| 120101300120 | 13 | 55 |
| 120101400120 | 14 | 59 |
| 120101600120 | 16 | 64 |

| | | |
|--------------|----|-----|
| 120101800120 | 18 | 73 |
| 120102000120 | 20 | 82 |
| 120102200120 | 22 | 91 |
| 120102400120 | 24 | 100 |
| 120102600120 | 26 | 109 |
| 120102800120 | 28 | 118 |
| 120103000120 | 30 | 127 |
| 120103200120 | 32 | 136 |
| 120103400120 | 34 | 146 |
| 120103600120 | 36 | 155 |
| 120103800120 | 38 | 164 |
| 120104000120 | 40 | 173 |
| 120104200120 | 42 | 182 |
| 120104400120 | 44 | 191 |
| 120104600120 | 46 | 200 |
| 120105000120 | 50 | 209 |
| 120105400120 | 54 | 228 |
| 120105800120 | 58 | 246 |
| 120106200120 | 62 | 264 |
| 120106600120 | 66 | 282 |
| 120107000120 | 70 | 300 |
| 120107400120 | 74 | 319 |
| 120107800120 | 78 | 337 |

120108200120

82

355

120109000120

90

391