

Ferrule TKH Talurit®



Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

Conical ferrule with an inspection hole to ensure the short end of the wire rope is correctly positioned after swaging. This hole remains open after swaging, due to the pressing in a die with a blind tap.

The ferrules can be used for fibre core, single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and some spiral strand ropes.

Material: Aluminium

Marking: According to standard

Standard: EN 13411-3

except size range

Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Part Code	Ferrule size mm	Length mm
120100800200	8	36
120100900200	9	40
120101000200	10	45
120101100200	11	50
120101200200	12	54
120101300200	13	59
120101400200	14	63

120101600200	16	72
120101800200	18	81
120102000200	20	90
120102200200	22	99
120102400200	24	108
120102600200	26	117
120102800200	28	126
120103000200	30	135
120103200200	32	144
120103400200	34	153
120103600200	36	162
120103800200	38	171
120104000200	40	180
120104400200	44	198
120105000200	50	228
120105400200	54	246
120104200200	42	-