

HPJ S Hydraulic Pulling Cylinder

Product information



Holmatro pulling cylinders (HPJ) – Spring return

Unique specifications:

- Compact
- Suitable for pulling, lifting, tensioning in all positions
- Protected against over pressure; A418 valve

Standard supplied with:

- High flow female coupler A118, with pressure relief valve A418

Accessories:

- Pulling eyes (art. No 100.181.051) and clevis eyes (art. No 100.181.056): 2 of both per cylinder = mandatory
- Protection spring (art. No. 100.581.160) = optional

Also available:

- Accessories
- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

Material: Steel

Note: Protection Spring, Pulling eyes and clevis eyes to be ordered separately (2 pcs per cylinder)

| Part code | Code | WLL ton | stroke length mm | required oil cc | A mm | B mm | C mm | D2 mm | F mm | G mm | H tread size | J mm | P mm | Weight kg |
|---------------|-------------|---------|------------------|-----------------|------|------|------|-------|------|------|--------------|------|------|-----------|
| 5211100131001 | HPJ 11 S 15 | 11 | 150 | 236 | 320 | 92 | 40 | 85 | 250 | 470 | M38x1.5 | 30 | 38 | 11.5 |
| 5211100131011 | HPJ 30 S 15 | 30 | 150 | 623 | 470 | 118 | 40 | 85 | 380 | 620 | M38x1.5 | 40 | 44 | 26 |
| 5211100131021 | HPJ 60 S 15 | 60 | 150 | 1,272 | 530 | 157 | 60 | 85 | 400 | 680 | M54x1.5 | 60 | 52 | 45 |

Blueprint

