



Lifting Eye Super Point 8-251

Product information



Pivots to 230°, rotates through 360° due to its unique ball bearing design.

Certified by DGUV GS-OA-15-04.

Load rated parts are 100% magnaflux crack detected.

Individual forged parts and batch code links to Test Certificate sheet.

Bolt are Metric thread (ASME / ANSI B18.3.1M).

Proof tested to 2.5 times the WLL.

Fatigue rated to 1.5 times the WLL.

All YOKE Super points meet or exceed all the requirements of ASME B30.26.

Easy to attach or dismantle due to the forged hexagon shaped body of the Super Point.

Capable of rotating under load.

With the new WLL tables you can find the right Super Point attachment for your application and by the red marking on both sides you can measure disposal stage of the Super Point.

Features: Built-in RFID/NFC chip

Material: Forged alloy steel, quenched and tempered.

Marking: According to standard, CE-marked

Temperature range: -40°C - +200°C

Standard: EN 1677-1

Warning: Do not turn continuously in 90 degree direction at full load.

Safety factor: 4:1

Part Code	WLL ton	Thread mm	Torque Nm	Pitch DIN13	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	K mm	M mm	Weight kg
4215825100401	0.3	M8	10-40	1.25	35	53	48	13	12	101	36.5	20.5	34	M8	0.3
4215825100701	0.5	M10	10-40	1.5	35	53	48	13	18	101	36.5	20.5	34	M10	0.4
4215825100702	0.7	M12	15-40	1.75	35	53	48	13	18	101	36.5	20.5	34	M12	0.4
4215825101401	1.4	M16	45-130	2	35	53	48	13	20	101	36.5	20.5	34	M16	0.44
4215825102501	2.5	M20	100-170	2.5	35	59	68	16	30	127	52	28	46	M20	1
4215825104001	4	M24	190-280	3	40	73	75	19	30	148	57	34.5	50	M24	1.5
4215825106701	6.7	M30	230-400	3.5	40	68	95	19	35	163	70	41	65	M30	2.4
4215825108001	8	M30	270-600	3.5	50	95	106	22	35	201	81	48	75	M30	3.6
4215825110001	10	M36	270-600	4	50	95	106	22	50	201	81	48	75	M36	3.8
4215825112502	12.5	M42	270-700	4.5	50	95	106	22	60	201	81	48	75	M42	4
4215825117005	18	M56	350-900	5.5	70	129	127	32	78	256	104	58	95	M56	8.1
4215825128001	28	M64	500-1000	6	80	131	174	36	96	305	129	78	115	M64	16.4

Technical data

Kind of attachment											
	1 0°	2 0°	1 90°	2 90°	2 0-45°	2 45-60°	2 unsymm.	3-4 0-45°	3-4 45-60°	3-4 unsymm.	
Number of legs	1	2	1	2	2	2	2	3-4	3-4	3-4	
Load direction	0°	0°	90°	90°	0-45°	45-60°	unsymm.	0-45°	45-60°	unsymm.	
Item No.	t	t	t	t	t	t	t	t	t	t	
8-251-007-01	M10	1	2	0.5	1	0.7	0.5	0.5	1	0.75	0.75
8-251-007-02	M12	1.4	2.8	0.7	1.4	1	0.7	0.7	1.4	1	1
8-251-007-03	M12	1.4	2.8	0.7	1.4	1	0.7	0.7	1.4	1	1
8-251-007-04	M14	2	4	1	2	1.4	1	1	2.12	1.5	1.5
8-251-014-01	M16	2.8	5.6	1.4	2.8	2	1.4	1.4	3	2.12	2.12
8-251-014-02	M16	2.8	5.6	1.4	2.8	2	1.4	1.4	3	2.12	2.12
8-251-014-03	M16	2.8	5.6	1.4	2.8	2	1.4	1.4	3	2.12	2.12
8-251-014-04	M20	3.4	6.8	1.7	3.4	2.4	1.7	1.7	3.55	2.5	2.5
8-251-014-05	M24	3.4	6.8	1.7	3.4	2.4	1.7	1.7	3.55	2.5	2.5
8-251-025-01	M20	5	10	2.5	5	3.55	2.5	2.5	5.3	3.75	3.75
8-251-025-02	M20	5	10	2.5	5	3.55	2.5	2.5	5.3	3.75	3.75
8-251-025-03	M20	5	10	2.5	5	3.55	2.5	2.5	5.3	3.75	3.75
8-251-025-04	M20	5	10	2.5	5	3.55	2.5	2.5	5.3	3.75	3.75
8-251-040-01	M24	8	16	4	8	5.6	4	4	8.5	6	6
8-251-040-02	M24	8	16	4	8	5.6	4	4	8.5	6	6
8-251-040-03	M24	8	16	4	8	5.6	4	4	8.5	6	6
8-251-040-04	M24	8	16	4	8	5.6	4	4	8.5	6	6
8-251-040-05	M30	8	16	4	8	5.6	4	4	8.5	6	6
8-251-067-01	M30	12	24	6.7	13.4	9.5	6.7	6.7	14	10	10
8-251-067-02	M30	12	24	6.7	13.4	9.5	6.7	6.7	14	10	10
8-251-067-03	M30	12	24	6.7	13.4	9.5	6.7	6.7	14	10	10
8-251-067-04	M30	12	24	6.7	13.4	9.5	6.7	6.7	14	10	10
8-251-080-01	M30	12	24	8	16	11.2	8	8	16	12	12
8-251-080-02	M30	12	24	8	16	11.2	8	8	16	12	12
8-251-100-01	M36	15	30	10	20	14	10	10	21.2	15	15
8-251-100-02	M36	15	30	10	20	14	10	10	21.2	15	15
8-251-125-01	M42	15	30	12.5	25	17	12.5	12.5	25	18	18
8-251-125-02	M42	15	30	12.5	25	17	12.5	12.5	25	18	18
8-251-125-03	M42	15	30	12.5	25	17	12.5	12.5	25	18	18
8-251-125-04	M45	15	30	12.5	25	17	12.5	12.5	25	18	18
8-251-125-05	M48	15	30	12.5	25	17	12.5	12.5	25	18	18
8-251-170-01	M42	20	40	13	26	18	13	13	27	19	19
8-251-170-02	M45	25	50	17	34	23.5	17	17	35	25	25
8-251-170-03	M48	25	50	17	34	23.5	17	17	35	25	25
8-251-170-04	M48	25	50	17	34	23.5	17	17	35	25	25
8-251-170-05	M56	25	50	18	36	25	18	18	37.5	26.5	26.5
8-251-170-06	M56	25	50	18	36	25	18	18	37.5	26.5	26.5
8-251-200-01	M64	25	50	20	40	28	20	20	42.5	30	30
8-251-200-02	M64	25	50	20	40	28	20	20	42.5	30	30
8-251-280-01	M64	32.5	65	28	56	39	28	28	58	42	42
8-251-280-02	M72	32.5	65	28	56	39	28	28	58	42	42
8-251-280-03	M80	32.5	65	28	56	39	28	28	58	42	42
8-251-350-01	M80	40	80	35	70	49	35	35	74	52.5	52.5
8-251-350-02	M90	40	80	35	70	49	35	35	74	52.5	52.5
8-251-400-01	M80	50	100	40	80	56	40	40	84	60	60
8-251-400-02	M90	50	100	40	80	56	40	40	84	60	60
8-251-400-03	M90	50	100	40	80	56	40	40	84	60	60
8-251-400-04	M100	50	100	40	80	56	40	40	84	60	60

Blueprint

