



ROV Sling Shackle with Locking Clamp Green Pin® P-6065

Product information

The Green Pin® Locking Clamp ROV Sling Shackle is perfect for release operations with remotely operated vehicles (ROV). The shackle has been specially developed for sub-sea applications and is easy to handle for the ROV pilot.

The Locking Clamp ROV Sling Shackle is an excellent choice due to the shape of the shackle crown. Compared to the standard Green Pin® Shackles, Sling Shackles have an increased bow radius to improve your sling's resistance to wear and tear and enable you to use a lighter rope to lift the same heavy load. This means that by using the Green Pin® Locking Clamp ROV Sling Shackle you can save on rope costs.

The ROV Sling Shackle has a powerful locking system that ensures that the load will not be released before you want it to. The white coating optimizes visibility underwater and ensures its long-term durability.

Material: Bow and Pin Alloy Steel, Quenched and Tempered

Temperature range: -20°C up to +200°C

Finish: Shackle bow painted white, Pin painted green

Safety factor: 5:1

Grade: 8

Part Code	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	l mm	Weight kg
420101252250	12.5	28	28	61	25	44	121	82	197	143	146	31	54	4.27
420101802250	18	35	35	69	30	54	148	102	239	184	180	31	64	6.85
420103002250	30	40	42	90	35	69	165	126	279	210	200	40	79	12.5
420104002250	40	55	51	109	45	84	199	140	331	256	235	40	97	20.3
420105502250	55	60	57	115	55	90	240	160	389	289	270	40	100	30.4
420107502250	75	68	70	125	54	110	290	185	473	317	317	40	120	45
420112502250	125	85	80	154	85	137	366	220	583	413	390	40	150	92
420115002250	150	94	95	179	89	147	391	253	645	445	434	55	170	140
420120002250	200	110	105	199	100	158	481	280	759	480	482	55	205	205
420125002250	250	126	120	227	110	179	542	300	859	523	530	55	240	264
420130002250	300	135	134	245	122	195	601	350	947	563	620	55	265	360

Blueprint

