

Product information





Auto crane hook, allows you to remotely attach and release loads with no handling. It catches the masterlink with a magnet, a sensor indicates when the ring is in the right position, and a reinforced safety latch keeps the load safely attached during lifting.

10 and 20 tons are available in a Compact version (C)

Material: Body: WELDOX® high strength steel body.

Temperature range: -20°C up to +85°C.

| Part Code | WLL ton | Model | Max. releasable weight kg | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | I mm | J mm | K mm | L mm | M mm | Weight kg |
|--------------|------------|-------|------------------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 420500500080 | 5 | evo5 | 15-30 | 277 | 170 | 469 | 409 | 194 | 43 | 49 | 57.6 | 25 | 41 | 58 | 350 | 15 | 26 |
| 420501000080 | 10 | evo10 | 20 | 342 | 182.3 | 584 | 485 | 246 | 66 | 68 | 83 | 42 | 72 | 82 | 400,4 | 22 | 36 |
| 420502000080 | 20 | evo20 | 20 | 341 | 182.3 | 663 | 553 | 246 | 66 | 105 | 83 | 42 | 72 | 115 | 480 | 29 | 43 |

Blueprint

