

Black Belt Sling Extreema® with HMPE core

Product information

These EXTREEMA® HMPE soft slings have an extensive track record and a solid global footprint in the heavy lift industry. The Black Belt $Sling^{TM}$ has unparalleled load-bearing capacity, ensuring the safe and efficient lifting of even the heaviest loads.

The core is made of general HMPE (Trosar®), which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is an orange PES inner sleeve and is covered with a black knitted Cordur[®] outer sleeve, which is known for its resistance to abrasions, tears, and scuffs. The black sleeve is repairable.

Features:

- · Lightweight and flexible, easy to handle
- Repairable sleeve
- Does not absorb water
- · Floats on water
- · Abrasion, tearing and scuff resistant
- Sustainable
- High pressure resistant
- EWL: 0,5m 65m

Material: PES, Dyneema

Marking: According to standard, CE-marked Temperature range: -50°C up to +70°C

Standard: EN 1492-2

Safety factor: 7:1

Part Code	WLL ton
340501000500140	10
340503001800140	30

340504	000200140	40
340504	000600140	40
340504	000400140	40
340505	000600140	50
340505	000300140	50
340505	000600142	50
340507	500050140	75
340507	500480140	75
340508	000410140	80
340508	000440140	80
340508	500100140	85
340508	500200140	85
340508	500300140	85
340508	500400140	85
340508	500870140	85
340510	000500140	100
340510	000600140	100
340510	001000140	100
340510	001200140	100
340512	000200140	120
340512	000700140	120
340512	500200140	125
340512	500400140	125

340515001500140	150
340516000700140	160
340518000500140	180
340518000600140	180
340520001000140	200
340520000600140	200
340520000400140	200
340525000300140	250
340525000500140	250
340525000700140	250
340525000800140	250