



Wire Rope Lifting Sling WLS-473

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²

Design: Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

| Part Code | WLL ton |
|-----------|---------|
| 1609 | 0.25 |
| 1609 | 0.44 |
| 1609 | 0.68 |
| 1609 | 0.98 |
| 1609 | 1.34 |
| 1609 | 1.72 |
| 1609 | 2.18 |
| 1609 | 2.69 |

| | |
|------|------|
| 1609 | 3.25 |
|------|------|

| | |
|------|------|
| 1609 | 3.85 |
|------|------|

| | |
|------|------|
| 1609 | 4.55 |
|------|------|

| | |
|------|------|
| 1609 | 5.28 |
|------|------|

| | |
|------|-----|
| 1609 | 6.9 |
|------|-----|

| | |
|------|------|
| 1609 | 8.71 |
|------|------|

| | |
|------|-------|
| 1609 | 10.75 |
|------|-------|

| | |
|------|-------|
| 1609 | 13.03 |
|------|-------|

| | |
|------|------|
| 1609 | 15.5 |
|------|------|

| | |
|------|-------|
| 1609 | 18.19 |
|------|-------|

| | |
|------|-------|
| 1609 | 21.08 |
|------|-------|

| | |
|------|-------|
| 1609 | 27.56 |
|------|-------|

| | |
|------|-------|
| 1609 | 34.84 |
|------|-------|

| | |
|------|-------|
| 1609 | 43.17 |
|------|-------|

| | |
|------|-------|
| 1609 | 52.04 |
|------|-------|

| | |
|------|-------|
| 1609 | 62.06 |
|------|-------|

| | |
|------|-------|
| 1609 | 75.85 |
|------|-------|

Technical data