



Fast Reeve Crane Blocks 5 sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Part Code	WLL ton	Model	For wire Ø mm	Hooksize	B mm	L mm	O mm	T mm	TA mm	TB mm	TL mm	Ø D1 mm	Ø D2 mm	Ø Z mm	Weight kg
6097FRB35516550E	50	FRB 355 .16 .5 .50 .E	16	12	959	1,342	84	28	500	382	1,224	410	355	32	500
6097FRB36019563E	63	FRB 360 .19 .5 .63 .E	19	16	973	1,375	97	30	510	422	1,243	420	360	37	600
6097FRB40019563E	63	FRB 400 .19 .5 .63 .E	19	16	1,048	1,520	97	30	570	432	1,388	460	400	37	750
6097FRB45022580E	80	FRB 450 .22 .5 .80 .E	22	20	1,188	1,730	110	30	600	437	1,580	515	450	43	815
6097FRB45024580E	80	FRB 450 .24 .5 .80 .E	24	20	1,188	1,730	110	40	600	437	1,580	515	450	52	815
6097FRB36019580E	80	FRB 360 .19 .5 .80 .E	19	20	1,082	1,502	110	30	510	482	1,352	420	360	37	820
6097FRB40019580E	80	FRB 400 .19 .5 .80 .E	19	20	1,147	1,597	110	30	570	507	1,447	460	400	37	820
6097FRB450245100E	100	FRB 450 .24 .5 .100 .E	24	25	1,263	1,768	132	45	600	417	1,598	515	450	52	910
6097FRB450265100EA	100	FRB 450 .26 .5 .100 .E .A	26	25	1,263	1,768	132	40	600	417	1,598	515	450	52	910
6097FRB450265100EB	100	FRB 450 .26 .5 .100 .E .B	26	25	1,263	1,768	132	40	600	507	1,598	515	450	52	1,140
6097FRB528245125E	125	FRB 528 .24 .5 .125 .E	24	32	1,333	1,913	137	45	710	622	1,723	595	528	52	1,820
6097FRB528265125E	125	FRB 528 .26 .5 .125 .E	26	32	1,333	1,913	137	45	710	622	1,723	595	528	52	1,820
6097FRB528285125E	125	FRB 528 .28 .5 .125 .E	28	32	1,333	1,913	137	50	710	622	1,723	595	528	59	1,820
6097FRB528265150E	150	FRB 528 .26 .5 .150 .E	26	40	1,333	1,935	167	50	710	602	1,723	595	528	52	1,820
6097FRB528285150E	150	FRB 528 .28 .5 .150 .E	28	40	1,333	1,938	167	50	710	622	1,726	595	528	59	1,820
6097FRB575285150E	150	FRB 575 .28 .5 .150 .E	28	40	1,383	2,015	167	50	770	572	1,803	650	575	52	1,820
6097FRB528285160E	160	FRB 528 .28 .5 .160 .E	28	40	1,502	2,191	167	50	710	662	1,979	595	528	59	2,270
6097FRB575285160E	160	FRB 575 .28 .5 .160 .E	28	40	1,591	2,223	167	50	770	592	2,011	650	575	59	2,270
6097FRB670285200E	200	FRB 670 .28 .5 .200 .E	28	50	1,716	2,442	188	50	870	782	2,206	760	670	59	3,560
6097FRB670325200E	200	FRB 670 .32 .5 .200 .E	32	50	1,716	2,442	188	60	870	782	2,206	760	670	66	3,560

Blueprint

