

Samson wire rope blocks 3 sheave



Product information

General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

Temperature range: -40°C / +80°C

Note: WLL= Working Load Limit on head fitting

Safety factor: 4:1

Part Code	WLL ton	For wire Ø mm	No of Sheaves	D1 mm	D2 mm	F mm	Ø G mm	Ø J mm	K mm	L mm	M mm	R mm	TA mm	TB mm	TL mm	Weight kg
424100200330	2	10	3	125	105	27	22	16	26	58	24	5,5	135	120	336	9
424100400330	4	12	3	150	120	40	30	26	40	94	33	6,5	170	166	468	17
424100600330	6	14	3	200	165	40	30	29	45	108	42	7,5	220	166	556	28
424100800330	8	18	3	250	210	45	35	32	49	114	45	9,5	270	185	633	46
424101000330	10	20	3	300	255	50	40	36	54	125	52	11	320	204	733	69
424101200330	12	22	3	350	305	50	45	41	60	144	56	12	380	212	823	99
424101600330	16	24	3	350	305	60	50	46	66	163	64	13	380	258	880	120
424101600335	16	24	3	400	345	60	50	46	66	163	64	13	430	250	927	157
424102000335	20	24	3	350	305	60	50	51	72	173	72	13	380	258	896	143
424102000330	20	24	3	400	345	60	60	51	72	173	72	13	430	266	1,006	184
424102500330	25	24	3	350	305	60	50	60	80	195	76	13	380	266	955	170
424102500335	25	24	3	400	345	60	60	60	80	195	76	13	430	266	1,065	198
424102500336	25	28	3	450	390	70	70	60	80	195	76	15	480	296	1,120	220
424103000330	30	28	3	400	345	60	60	60	90	220	80	15	430	266	1,095	215
424103000335	30	28	3	450	390	70	70	60	90	220	80	15	480	296	1,140	255
424104000330	40	28	3	400	345	60	60	-	96	96	90	15	430	278	945	250
424104000335	40	28	3	450	390	70	70	-	96	96	90	15	480	308	1,030	295
424105000330	50	28	3	450	390	70	75	-	106	106	100	15	480	338	1,055	335

Blueprint

