



Standard Reeve Crane Blocks 4 sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Part Code	WLL ton	Model no.	For wire Ø mm	Hooksize	Ø D1 mm	Ø D2 mm	B mm	O mm	TA mm	TB mm	TL mm	L mm	T mm	Ø Z mm	Weight kg
6097SRB28516435E	35	SRB 285 .16 .4 .35 .E	16	10	325	285	660	76	400	346	920	1,026	28	32	260
6097SRB35519450E	50	SRB 355 .19 .4 .50 .E	19	16	410	355	839	97	500	392	1,114	1,291	35	37	475
6097SRB40022463E	63	SRB 400 .22 .4 .63 .E	22	16	460	400	905	97	570	373	1,200	1,382	40	43	525
6097SRB45022463E	63	SRB 450 .22 .4 .63 .E	22	16	515	450	965	97	600	413	1,321	1,503	40	43	725
6097SRB45024480E	80	SRB 450 .24 .4 .80 .E	24	20	515	450	1,047	110	600	493	1,310	1,520	45	52	960
6097SRB45026480E	80	SRB 450 .26 .4 .80 .E	26	20	515	450	1,047	110	600	493	1,310	1,520	45	52	960
6097SRB528264100E	100	SRB 528 .26 .4 .100 .E	26	25	595	528	1,223	132	710	512	1,593	1,823	45	52	1,250
6097SRB528284100E	100	SRB 528 .28 .4 .100 .E	28	25	595	528	1,223	132	710	512	1,593	1,833	50	59	1,250
6097SRB670284160E	160	SRB 670 .28 .4 .160 .E	28	40	760	670	1,541	167	870	682	2,106	2,388	50	59	3,150
6097SRB670324160E	160	SRB 670 .32 .4 .160 .E	32	40	760	670	1,541	167	870	682	2,106	2,393	60	66	3,150