

Lifting Chain Short Link +200°C

Product information



European quality short link chain approved for lifting and lashing.

Marking: According to standard, At least every 20th link, or at least one link per meter.

Temperature range: -40°C up to +200°C.

Finish: Painted.

Standard: EN 818-2

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	Min. Breaking force, kN	Pitch Length	d mm	p mm	w1 mm	w2	Weight kg/m
203500500000150	5	1	39.3	15	5	15	6.5	18.5	0.56
203500600000150	6	1.4	56.5	18	6	18	8.5	22.2	0.9
203500700000150	7	1.9	77	21	7	21	9.1	25.9	1.2
203500800000150	8	2.5	101	24	8	24	11	29.6	1.6
203501000000150	10	4	157	30	10	30	13.5	37	2.5
203501300000150	13	6.7	265	39	13	39	16.9	48.1	4.2
203501600000150	16	10	402	48	16	48	20.8	59.2	6.2
203501900000150	19	14	567	57	19	57	24.7	70.3	9
203502000000150	20	16	628	60	20	60	26	74	10
203502200000150	22	19	760	66	22	66	28.6	81.4	11.9
203502600000150	26	26.5	1,060	78	26	78	33.8	96.2	16.3
203503200000150	32	40	1,610	96	32	96	41.6	118	24.3

Blueprint

