



## Eye sling hook with latch, grade 80

### Product information

Hook is equipped with spring loaded safety latch.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	EWL mm	For chain dia. mm	K mm	E mm	F mm	R mm	A mm	Weight kg
401300110680	1.12	76	6	108	24	9	21	20	0.3
401300200680	2	90	7/8	133	30	11	26	25	0.4
401300320680	3.15	117	10	167	34	15	39	38	0.9
401300530680	5.3	152	13	213	39	19	54	43	1.7
401300800680	8	178	16	255	46	23	64	50	3.2
401301250680	12.5	226	20	305	40	24	80	62	5.8
401301500680	15	249	22	348	71	32	80	62	8.5
401302120680	21.2	284	26	394	81	35	82	64	13
401303150680	31.5	346	32	480	102	37	112	68	17

## Technical data

**SPARE PARTS****Spare part set (product code) | Inc. latch, spring and pin/nut****Fits the hook (product code)**

SALKVO6S

SALK6

SALKVO78S

SALK78

SALKVO10S

SALK10

SALKVO13S

SALK13

SALKVO16S

SALK16

SALKVO20S

SALK20

SALKVO22S

SALK22

SALKVO26S

SALK26

SALKVO32S

SALK32

# Blueprint

