



## Eye sling hook with latch, grade 80

### Product information

Hook is equipped with spring loaded safety latch.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

| Part Code    | WLL<br>ton | EWL<br>mm | For chain dia.<br>mm | K<br>mm | E<br>mm | F<br>mm | R<br>mm | A<br>mm | Weight<br>kg |
|--------------|------------|-----------|----------------------|---------|---------|---------|---------|---------|--------------|
| 401300110680 | 1.12       | 76        | 6                    | 108     | 24      | 9       | 21      | 20      | 0.3          |
| 401300200680 | 2          | 90        | 7/8                  | 133     | 30      | 11      | 26      | 25      | 0.4          |
| 401300320680 | 3.15       | 117       | 10                   | 167     | 34      | 15      | 39      | 38      | 0.9          |
| 401300530680 | 5.3        | 152       | 13                   | 213     | 39      | 19      | 54      | 43      | 1.7          |
| 401300800680 | 8          | 178       | 16                   | 255     | 46      | 23      | 64      | 50      | 3.2          |
| 401301250680 | 12.5       | 226       | 20                   | 305     | 40      | 24      | 80      | 62      | 5.8          |
| 401301500680 | 15         | 249       | 22                   | 348     | 71      | 32      | 80      | 62      | 8.5          |
| 401302120680 | 21.2       | 284       | 26                   | 394     | 81      | 35      | 82      | 64      | 13           |
| 401303150680 | 31.5       | 346       | 32                   | 480     | 102     | 37      | 112     | 68      | 17           |

## Technical data

**SPARE PARTS****Spare part set (product code) | Inc. latch, spring and pin/nut****Fits the hook (product code)**

SALKVO6S

SALK6

SALKVO78S

SALK78

SALKVO10S

SALK10

SALKVO13S

SALK13

SALKVO16S

SALK16

SALKVO20S

SALK20

SALKVO22S

SALK22

SALKVO26S

SALK26

SALKVO32S

SALK32

# Blueprint

