



## Eye self-locking hook with ball bearing swivel, grade 80

### Product information

The hook locks automatically when lifting starts and rotates easily also with full load.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-3

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part code	WLL ton	EWL mm	For chain Ø mm	A mm	B mm	C mm	L1 mm	L mm	T mm	E mm	M mm	N mm	Ø mm	Weight kg
420500110890	1.12	160	6	32	11	34	160	194	28	32	70	15	34	0.71
420500200890	2	202	7/8	36	13	40	202	240	35	39	88	20	44	1.1
420500320890	3.15	283	10	42	16	48	237	283	45	48	108	26	58	2
420500530890	5.3	282	13	50	17	58	282	343	52	65	134	33	70	4
420500800890	8	342	16	61	22	60	342	419	63	65	169	38	86	7.3
420501250890	12.5	483	20	76	27	75	400	483	86	85	186	50	97	11.6
420501500890	15	564	22	97	33	97	466	564	76	80	202	52	98	16

# Blueprint

