



Safety Hook WSB/S Grade 10 - Swivel

Product information

The standard type can not be swiveled when loaded. Not for the welded system!

Material: Alloy steel

Marking: According to standard, Code and grade

Finish: Violet powder coated.

Standard: EN 1677-3

(+ 25% WLL)

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | EWL mm | a mm | d2 mm | e mm | g mm | h mm | S max | w mm | w1 mm | Weight kg |
|--------------|--------------|---------|--------|------|-------|------|------|------|-------|------|-------|-----------|
| 420500140930 | WSB/S-6-10 | 1.4 | 161 | 17 | 12 | 161 | 28 | 20 | 1 | 35 | 36 | 1.2 |
| 420500250930 | WSB/S-7/8-10 | 2.5 | 182 | 20 | 12 | 182 | 34 | 26 | 1 | 35 | 36 | 1.54 |
| 420500400930 | WSB/S-10-10 | 4 | 218 | 29 | 16 | 218 | 45 | 30 | 1 | 42 | 40 | 2.14 |
| 420500670930 | WSB/S-13-10 | 6.7 | 269 | 35 | 20 | 269 | 52 | 40 | 1.5 | 49 | 47 | 4.42 |
| 420501000930 | WSB/S-16-10 | 10 | 319 | 41 | 24 | 319 | 60 | 50 | 2 | 60 | 60 | 7.34 |

Blueprint

