

Transport Anchor with cross hole Starcon



Product information

STARCON Transport Anchors with cross hole with inside thread for transport and fixing of concrete elements. The transport anchor with cross hole can be used together with the reinforcement bar which is bent and mounted in the lower cross hole. Using a transport anchor with cross hole is one of the best ways of lifting and fixing concrete wall elements or tunnel elements. Transport anchors with cross hole are also available with metric thread.

Material: Steel S355.

Marking: According to standard, Load Group+Starcon, batch code, CE.

Temperature range: 100°C.

Finish: Electro-galvanized (silver).

Standard: CEN/TR 15728 - VDI/BV-BS 6205

| Part Code | Dimensions mm | L mm | Ø D mm | e mm | ø g mm |
|----------------|------------------------------|---------|-----------|---------|-----------|
| 650530NK3012ZN | M12 X 60 MM WITH CROSS HOLE | 60 | 16 | 24 | 10 |
| 650530NK3016ZN | M16 X 79 MM WITH CROSS HOLE | 79 | 21 | 31 | 13 |
| 650530NK3020ZN | M20 X 99 MM WITH CROSS HOLE | 99 | 27 | 37 | 15 |
| 650530NK3024ZN | M24 X 110 MM WITH CROSS HOLE | 110 | 31 | 40 | 18 |
| 6501NK3030EG | M30 X 135 MM WITH CROSS HOLE | 135 | 39.5 | 45 | 20 |
| 650530NK3030ZN | M30 X 156 MM WITH CROSS HOLE | 156 | 39.5 | 56 | 20 |

Technical data

| Measures - reinforcement mm | | |
|-----------------------------|-----|-----|
| ds | G | D |
| 8 | 300 | 60 |
| 10 | 350 | 70 |
| 12 | 400 | 80 |
| 14 | 450 | 100 |
| 16 | 600 | 130 |
| 16 | 600 | 130 |

Blueprint

