



Transport Anchor with Cross Pin Starcon

Product information

Starcon transport anchors with cross pin with inside thread for transport and fixing of concrete elements.

The transport anchor with cross pin can be mounted directly to the reinforcement mesh in precast concrete elements. Using a transport anchor with cross pin is one of the best ways of lifting and fixing concrete wall elements or tunnel elements. Transport anchors with cross pin are also available with metric thread.

Material: Steel S355.

Marking: According to standard, Load Group+Starcon, batch code, CE.

Temperature range: 100°C.

Finish: Electro-galvanized (silver).

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Part Code	Thread mm	Load grp.	Length mm	M mm	L mm	D mm	E mm	Ø mm	L1 mm	F mm	Weight kg
650535NK3012ZNP	M12	0.5 t	60	M12	60	15	25	10	60	13	0.072
650535NK3016ZNP	M16	1.2 t	79	M16	79	21	32	12	80	20	0.172
650535NK3016100ZNP	M16	1.2 t	100	M16	100	21	32	12	100	20	0.232
650535NK3020ZNP	M20	2 t	99	M20	99	27.2	37	14	100	24	0.36
650535NK3020120ZNP	M20	2 t	120	M20	120	27.2	45	14	100	24	0.392
650535NK3024ZNP	M24	2.5 t	110	M24	110	31	45	14	100	24	0.43

Blueprint

