



## STA-S Spread Anchor

### Product information

Transport Anchor STA-S is suitable for loads from 0.7 up to 22.0 t and for use in both thin panels and plates. The head of the spread anchor has a hole in which the locking bolt of the lifting eye is mounted. Other holes in the anchor are for further reinforcement.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

**Marking:** CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

**Finish:** Untreated or hot dip galvanized

Part Code	Load grp.	Lenght mm	Finish	L mm	a mm	b mm	c mm	Hole mm	Weight kg
65012202501501	2.5	150	Untreated	150	30	14	10	14x20	0.32
65012202501502	2.5	150	HDG	150	30	14	10	14x20	0.32
65012202502001	2.5	200	Untreated	200	30	14	10	14x20	0.42
65012205001801	5	180	Untreated	180	40	20	10	20x22	0.75
65012205001802	5	180	HDG	180	40	20	10	20x22	0.78
65012205002401	5	240	Untreated	240	40	20	10	20x22	1.01
65012205002402	5	240	HDG	240	40	20	10	20x22	1.05
65012207502601	7.5	260	Untreated	260	60	26	16	26x30	1.68
65012207502602	7.5	260	HDG	260	60	26	16	26x30	1.8

## Blueprint

