



## STA-Z 2-Hole Anchor

### Product information

The 2-hole transport anchor STA-Z is suitable for loads from 0.7 up to 22.0 t. The STA-Z 2-hole anchor is almost similar to the transport anchor STA-S. The STA-Z 2-hole anchor, however, uses more reinforcement which is mounted through the lower hole. The head of the anchor has a hole in which the locking bolt of the ring clutch is mounted. Other holes in the anchor are meant for further reinforcement.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

**Marking:** CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

**Finish:** Untreated or hot dip galvanized

| Part Code      | Load grp. | Lenght mm | Finish    | L mm | a mm | b mm | c mm | Hole mm | Weight kg |
|----------------|-----------|-----------|-----------|------|------|------|------|---------|-----------|
| 65012602500901 | 2.5       | 90        | Untreated | 90   | 30   | 14   | 10   | 14x20   | 0.16      |
| 65012602500902 | 2.5       | 90        | HDG       | 90   | 30   | 14   | 10   | 14x20   | 0.17      |
| 65012605001201 | 5         | 120       | Untreated | 120  | 40   | 18   | 15   | 18x22   | 0.42      |
| 65012605001202 | 5         | 120       | HDG       | 120  | 40   | 18   | 15   | 18x22   | 0.42      |
| 65012607501601 | 7.5       | 160       | Untreated | 160  | 60   | 26   | 16   | 26x30   | 0.91      |
| 65012607501602 | 7.5       | 160       | HDG       | 160  | 60   | 26   | 16   | 26x30   | 0.92      |
| 65012610001701 | 10        | 170       | Untreated | 170  | 60   | 30   | 20   | 28x30   | 1.26      |
| 65012610001702 | 10        | 170       | HDG       | 170  | 60   | 30   | 20   | 28x30   | 1.26      |

# Blueprint

