



Clevis Foundry Hook X-046 Grade 10

Product information

At least 25% greater WLL than traditional Grade 8 products.
 Testing according to DIN PAS 1061 and ASTM A952/A 952M.
 Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
 Tempering temperature minimum 400°C.
 Designed for the assembly of chain slings where wide throat openings are necessary.

Material: Quenched and tempered alloy steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-1

Warning: Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

Safety factor: 4:1

Grade: 10

| Part Code | WLL ton | EWL | For chain Grade 10 Ø mm | A mm | H mm | K mm | P mm | T mm | Weight kg |
|--------------|------------|-----|----------------------------|---------|---------|---------|---------|---------|--------------|
| 402300250770 | 2.5 | 133 | 7,8 | 9 | 27 | 133 | 62 | 19 | 0.95 |
| 402300400770 | 4 | 163 | 10 | 11 | 32 | 163 | 74 | 23 | 1.8 |
| 402300670770 | 6.7 | 200 | 13 | 14 | 39 | 200 | 88 | 32 | 3.6 |

Blueprint

