

Welded Master Link Assembly X-0082



Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	EWL ton	Proof Load kN	For chain gr 10 Ø 2 leg mm	For chain gr 10 Ø 3-4 leg mm	WLL β 0-45° ton	Used to single hook acc. to DIN 15401 No.	D mm	A mm	B mm	d mm	a mm	b mm	Weight kg
402100360440	ED-22	3.55	394	87	6,7,8	6	3,55	25	22	340	180	13	54	25	3.2
402100560440	ED-28	5.6	374	137	10	7,8	5,6	25	28	340	180	16	70	34	5.4
402100950440	ED-32	9.5	425	233	13	10	9,5	25	32	340	180	19	85	40	7.4
402101410440	ED-40	14.1	455	343	16	13	14,1	25	40	340	180	22	115	50	12.1
402102110440	ED-40	21.2	480	519	20	16	21,2	25	40	340	180	25	140	65	14.2

Blueprint

