



## Welded Master Link Assembly X-0082

### Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.  
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.  
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	EWL	Proof Load kN	For chain gr 10 Ø 2 leg mm	For chain gr 10 Ø 3-4 leg mm	WLL 0-45° ton	Used to single hook acc. to DIN 15401 No.	Weight kg
402100360440	ED-22	3.55	394	87	6,7,8	6	3,55	25	3.2
402100560440	ED-28	5.6	374	137	10	7,8	5,6	25	5.4
402100950440	ED-32	9.5	425	233	13	10	9,5	25	7.4
402101410440	ED-40	14.1	455	343	16	13	14,1	25	12.1
402102110440	ED-40	21.2	480	519	20	16	21,2	25	14.2

# Blueprint

