



## 4 Special Clevis Sub-Assembly GTVK/SUN

### Product information

**General:** For 3 and 4-leg slings with shortening element.

**Temperature range:** -40 °C up to 200 °C

**Safety factor:** 4:1

**Grade:** 12

| Part Code    | Code          | WLL ton | EWL | Chain Ø mm | WLL 45-60° ton | Chain Ø inch | can be used with single hook acc. DIN15401 up to nr. | d mm | t mm | w mm | e mm | Weight kg |
|--------------|---------------|---------|-----|------------|----------------|--------------|--|------|------|------|------|-----------|
| 403100500080 | GTVK/SUN 4-7  | 5       | 368 | 7          | 3.55           | 9/32         | 10   | 27   | 190  | 110  | 368  | 6.35      |
| 403100630080 | GTVK/SUN 4-8  | 6.3     | 368 | 8          | 4.5            | 5/16         | 10   | 27   | 190  | 110  | 368  | 6.39      |
| 403101060080 | GTVK/SUN 4-10 | 10.6    | 433 | 10         | 7.5            | 3/8          | 12   | 30   | 190  | 110  | 433  | 10.94     |
| 403101700080 | GTVK/SUN 4-13 | 17      | 616 | 13         | 11.8           | 1/2          | 12   | 38   | 275  | 150  | 616  | 25.35     |
| 403102560080 | GTVK/SUN 4-16 | 25.6    | 658 | 16         | 18.3           | 5/8          | 12   | 38   | 275  | 150  | 658  | 37.17     |

# Blueprint

