



Chain Block POWERTEX PCB-S2OLP

Product information

POWERTEX



The PowerTex PCB-S2 OLP Chain Hoist is a high-quality chain block designed to provide durability, safety, and ease of operation. With its ergonomic hand chain, advanced features, and built-in overload protection, this chain hoist ensures smooth and efficient lifting for various industrial applications. This OLP version has an integrated Overload Protection, which ensures safe lifting and prevents unintended overloading of the hoist.

Product benefits:

- **Overload protection device:** the OLP hoists are factory-equipped with an Overload Protection device, which limits the maximum operating force that can be applied using the hand chain, ensuring safe and controlled lifting operations.
- **Enhanced safety:** each hoist undergoes dynamic proof load testing at 1.5 times the Working Load Limit (WLL) before leaving the factory, ensuring maximum safety and reliability. The hoist is equipped with a well-covered automatic load reaction brake and features double safety with two brake pawls and four brake springs, exceeding EN 13157 requirements. The load chain is calibrated, proof load tested and meets the requirements of EN 818-7.
- **Smooth and efficient operation:** the compact and lightweight construction, combined with a sprocket wheel equipped with needle bearings and a drive shaft supported by needle and slide bearings, ensures smooth and efficient operation. The fine-calibrated European-made COROLIM® protected load chain offers quiet and seamless performance.
- **Load chain with superior corrosion resistance:** the unique COROLIM® surface treatment of the load chain provides excellent corrosion protection, equivalent to ISO944-9 C5High / ISO9223 C3 standards, ensuring long-lasting durability even in harsh environments.
- **Easy positioning and safe hooks:** swivel hooks at both ends make in-line positioning easy. The hooks are designed to open at overload instead of breaking, enhancing safety. Heavy-duty steel safety latches and deformation check dots forged into the side of the hooks allow for easy overload detection.
- **Convenient maintenance and documentation:** each hoist is RFID-equipped for easy service and inspection, and a QR code provides on-site access to multilingual user manuals. A test certificate and Declaration of Conformity are enclosed with each hoist, ensuring compliance and traceability.
- **Available spare parts:** spare parts such as hooks, brake discs, safety latches, and chains are readily available, ensuring that maintenance and repairs can be carried out efficiently and further extending the hoist's service life.

Product options:

- **Chain bag:** an optional chain bag is available for added convenience and organization.

Material: Durable all steel construction

Marking: According to standard, CE-marked, UKCA-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code

Temperature range: -10°C up to +50°C

Finish: Red powder coated body and plated frame components

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Part Code	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Hand force max. kg	A mm	B mm	C mm	D mm	H min mm	Weight kg
500100050300181	0.5	3	1	PCB-S2OLP/500KG	5,0 x 15,0	5,0 x 23,7	24.9	130	128	22	34	280	9.8
500100050600181	0.5	6	1	PCB-S2OLP/500KG	5,0 x 15,0	5,0 x 23,7	24.9	130	128	22	34	280	9.8
500100100300181	1	3	1	PCB-S2OLP/1000KG	6,3 x 19,0	5,0 x 23,7	28.4	150	145	26	39	330	11.7
500100100600181	1	6	1	PCB-S2OLP/1000KG	6,3 x 19,0	5,0 x 23,7	28.4	150	145	26	39	330	12
500100200300181	2	3	1	PCB-S2OLP/2000KG	8,0 x 24,0	5,0 x 23,7	34.3	185	175	35	49	385	18.9
500100200600181	2	6	1	PCB-S2OLP/2000KG	8,0 x 24,0	5,0 x 23,7	34.3	185	175	35	49	385	19.5
500100300300181	3	3	2	PCB-S2OLP/3000KG	7,1 x 21,0	5,0 x 23,7	34.3	220	158	37	50	510	28.9
500100300600181	3	6	2	PCB-S2OLP/3000KG	7,1 x 21,0	5,0 x 23,7	34.3	220	158	37	50	510	28.9
500100500300181	5	3	2	PCB-S2OLP/5000KG	9,0 x 27,0	5,0 x 23,7	37.2	255	183	43	60	615	37.1
500100500600181	5	6	2	PCB-S2OLP/5000KG	9,0 x 27,0	5,0 x 23,7	37.2	255	183	43	60	615	51.05
500100750300181	7.5	3	3	PCB-S2OLP/7500KG	9,0 x 27,0	5,0 x 23,7	36.8	430	189	47	67	690	50
500100750600181	7.5	6	3	PCB-S2OLP/7500KG	9,0 x 27,0	5,0 x 23,7	36.8	430	189	47	67	690	66.2
500101000300181	10	3	4	PCB-S2OLP/10000KG	9,0 x 27,0	5,0 x 23,7	40	360	183	47	65	820	92.8
500101000600181	10	6	4	PCB-S2OLP/10000KG	9,0 x 27,0	5,0 x 23,7	40	360	183	47	65	820	114.4

Technical data

Blueprint



