



Haklift electric chain hoist 380 V

Product information

Robust electric chain hoist with induction motor. Product is equipped with chain bag and upper and lower limit switches as well as with thermal protection switch and over loading protector. Longer control and power cables and chains are available upon request.

Features: IP54

Material: Steel

Marking: CE-marked

Temperature range: -10° - (+) 50°

Finish: Painted, blue

| WLL ton | Lifting height m | Chain Ø mm | Chain falls | Duty rating % ED | Hoisting speed m/min | Hoist motor kW | Weight kg |
|---------|------------------|------------|-------------|------------------|----------------------|----------------|-----------|
| 1 | 6 | 7.1 | 1 | 40 | 6 | 1.47 | 53 |
| 2 | 6 | 7.1 | 2 | 40 | 3 | 1.47 | 61 |

Technical data

DIMENSIONS

| Product | Control cable m | Electric cable m | Body width mm | Body depth mm | Body + chain min height mm |
|----------|--------------------|---------------------|------------------|------------------|-------------------------------|
| SKTH1000 | 6 | 1,5 | 430 | 290 | 600 |
| SKTH2000 | 6 | 1,5 | 430 | 290 | 600 |

SPARE PARTS

| Spare part (product code) | Description | Suitable for hoist (product code/-s) |
|---------------------------|---|--------------------------------------|
| KAPULA3 | Pendant control for SKTH1000/-2000 | SKTH1000, SKTH2000 |
| KAPULA4 | Pendant control for SKTH1000/-2000 with trolley | (with SKTH2000MSIV) |

Also other spare parts available with a delivery time, ask our sales for more information