



Geared trolley

Product information

Geared trolley for IPE and T beams. The trolley moves on the beam by pulling the hand chain. The wheels are equipped with duration lubricated ball bearings. The width of the trolley can be adjusted by a threaded rod (10 and 20 t models with washers, in the picture). The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -10°C - (+)50°C

Finish: Painted, yellow

Standard: EN 13157

Safety factor: 4:1

Part Code	WLL ton	Beam width mm	Min. Radius Curve m	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
502600102200130	1	58-220	0.7	353.5	238	183	17	31	-3	68	95	12.5
502600202200130	2	66-220	0.9	362	277	208	20	31	-3	80	108	17
502600302200130	3	74-220	1.2	406.5	324	249	26	31	-3	100	131	28
502600502200130	5	90-220	1	434.5	373	296.5	28	40	-5	120	154	45
502601002030130	10	125-203	1.3	487.5	455	490	82	36.5	-5	-	-	93
502602002030130	20	136-203	4.7	523	642	622	110	54	-5	-	-	247.5

Blueprint

