



Control Valves

Product information

General: Control valve VM 43.

Features and benefits:

- Suitable for double-acting tools.
- Handle stops in each position.
- With pressure controlled non-return valves for securing the load.
- 3-position 4-way valve.
- Connection: 3/8" NPT female (2x)

Part Code	Model	Description
5201	VM 43 L	• Suitable for double-acting tools• Handle stops in each position• With pressure controlled non-return valves forsecuring the load• 3-position 4-way valve• Connection: 3/8" NPT female (2x)
5201	M 311	• Suitable for single-acting tools• Handle stops in each position• 3-position, 3-way Valve• Not in combination with a vari pump model(name) starting with 18 W• Connection 3/8" NPT female thread (2x)
5201	M 322	• Suitbale for double-acting tools• Handle stops in each position• With pressure-controlled non-return valves forsecuring the load• 3-position 4-way Valve• Connection: 3/8" NPT female (2x)
5201	M 323 • 9	Suitable for double-acting tools• Handle with dead man's function, automaticallygoes to "O" position• With pressure-controlled non-return valves forsecuring the load• 3-position, 4-way Valve• Connection: 3/8" NPT female (2x)
5201	M 304	• For assembly on the varipump underneath adouble-acting valve (M 322, M 323, M324 or M 325)• This valve makes it possible to drive both singleand double acting tools with just one pump• Switch with A + B function (double-acting) or A(single-acting)