



Alloy Swivel Bearing Hoist Hook 8-175N

Informacja o produkcie

Built with ball bearing and enables full swivel feature under load. At least 25% greater WLL than traditional Grade 8 products. Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch.

Znakowanie: zgodnie z normą
standard: EN 1677-1

Współczynnik bezpieczeństwa: 4:1
Klasa: 10

Nr artykułu	Średnica łańcucha mm	DOR ton	Typ	A mm	B mm	C mm	D mm	G	H mm	K	L	P mm	P1 mm	T mm	Waga kg
420500200660	7-8	2	CC	36	29	26	13	91	25	143	181	24	20	22	0,9
420500300660	10	3	DD	41	35	29	16	102	29	172	217	28	25	24	1,6
420500500660	13	5	EE	46	44	38	21	130	36	211	269	35	31	31	3,2
420500700660	16	7	FF	61	51	49	23	166	46	258	328	43	39	42	5,7
420501100660	20	11	GG	74	82	62	25	196	58	326	409	61	57	48	9,5
420501500660	22	15	HH	97	96	65	33	221	64	372	471	72	62	56	16

Rysunek techniczny

