

Kausza DIN 6899B

Informacja o produkcie

Konstrukcja: Tłoczone z profilowanej stali.

Zakończenie: Ocynkowane



Nr artykułu	Średnica liny mm	a	b mm	c	d mm	e mm	Waga kg/100pcs
123100250010	2,5	3	22	19	12	1,6	0,6
123100350010	3,5	4	26	21	13	1,6	0,7
123100400010	4	5	32	23	14	1,9	0,9
123100500010	5	6	38	25	16	2,4	1,8
123100600010	6	7	44	28	18	2,4	1,9
123100700010	7	8	51	32	20	2,8	2,7
123100900010	9	10	57	38	24	3,1	4,1
123101100010	11	12	64	45	28	3,3	6,9

123101200010	12	13	70	48	30	3,3	7,6
123101300010	13	14	76	51	32	3,7	9,2
123101500010	15	16	83	58	36	3,8	16,4
123101600010	16	17	89	61	38	4,7	19
123101700010	17	18	95	64	40	4,7	20,3
123101800010	18	20	102	72	45	5,7	27,3
123102000010	20	22	114	80	50	5,7	28,6
123102200010	22	24	127	90	56	6,5	44,8
123102400010	24	26	140	99	62	6,8	57,7
123102600010	26	28	152	112	70	8	72
123103400010	34	36	216	160	100	8,5	176
123103600010	36	38	229	176	110	8,5	195
123103800010	38	40	241	184	115	10,5	292
123104000010	40	42	254	192	120	10,5	320
123104200010	42	45	305	240	150	10,5	364
123104700010	47	50	360	265	160	12	535
123105700010	57	60	380	275	170	12	790
123106300010	63	65	420	300	180	13	830
123107200010	72	75	460	350	200	15	1 200
123109700010	97	100	550	380	220	20	3 050

Rysunek techniczny

