

Kausza z stali nierdzewnej



Informacja o produkcie



Tłoczone z profilowanej stali. Pierwszy wybór dla surowego środowiska w sektorze morskim.

Materiał: Nierdzewna stal kwasoodporna AISI 316.

Zakończenie: Polerowany

| Nr artykułu | Średnica liny mm | A mm | B mm | L | S mm | Waga kg/100pcs |
|--------------|---------------------|------|------|----|------|-------------------|
| 123100200190 | 2 | 3 | 9 | 16 | 1,0 | 0,2 |
| 123100300190 | 3 | 4 | 10 | 17 | 1,0 | 0,3 |
| 123100400190 | 4 | 5 | 11 | 19 | 1,35 | 0,5 |
| 123100500190 | 5 | 6 | 13 | 21 | 1,2 | 0,7 |
| 123100600190 | 6 | 7 | 15 | 27 | 1,5 | 1,1 |
| 123100700190 | 7 | 8 | 19 | 33 | 1,5 | 1,4 |
| 123100800190 | 8 | 9 | 22 | 38 | 2,0 | 2,6 |
| 123100900190 | 9 | 10 | 24 | 43 | 2,0 | 3,1 |

| | | | | | | |
|--------------|----|----|-----|-----|------|------|
| 123101000190 | 10 | 11 | 27 | 46 | 2,7 | 4,9 |
| 123101200190 | 12 | 14 | 29 | 52 | 2,7 | 6,6 |
| 123101400190 | 14 | 16 | 33 | 57 | 3,0 | 9 |
| 123101600190 | 16 | 18 | 40 | 67 | 3,0 | 11,3 |
| 123101800190 | 18 | 20 | 45 | 75 | 4,0 | 19 |
| 123102000190 | 20 | 22 | 52 | 84 | 4,0 | 31,2 |
| 123102200190 | 22 | 24 | 56 | 93 | 5,0 | 45,5 |
| 123102600190 | 26 | 28 | 65 | 112 | 6,0 | 67 |
| 123102800190 | 28 | 30 | 80 | 135 | 5,5 | 82 |
| 123103200190 | 32 | 34 | 92 | 160 | 6,25 | 110 |
| 123103400190 | 34 | 36 | 105 | 160 | 6,0 | 117 |
| 123103600190 | 36 | 38 | 115 | 176 | 6,0 | 142 |
| 123103800190 | 38 | 40 | 120 | 180 | 8,0 | 206 |
| 123104000190 | 40 | 42 | 120 | 192 | 8,0 | 220 |
| 123104200190 | 42 | 45 | 150 | 240 | 8,0 | 304 |

Rysunek techniczny

