



Lifting Eye RUD VLBG

Product information

- Captive but exchangeable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads

Safety factor: 4:1

| Код товара | Код | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | I mm | K mm | L mm | M mm | N mm | T mm | Вес kg |
|-------------|----------|---------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|--------|
| 42158600399 | VLBG-M14 | 1,2 | 33 | 56 | 36 | 30 | 39 | 13,5 | 36 | 21 | 86 | 47 | 57 | M14 | 38 | 85 | 0,52 |
| 42158600384 | VLBG-M18 | 2 | 50 | 82 | 54 | 45 | 55 | 16,5 | 43 | 27 | 113 | 64 | 70 | M18 | 48 | 110 | 1,3 |
| 42158600385 | VLBG-M22 | 2,5 | 50 | 82 | 54 | 45 | 54 | 16,5 | 43 | 33 | 113 | 64 | 75 | M22 | 48 | 110 | 1,31 |
| 42157983658 | VLBG-M27 | 4 | 60 | 103 | 65 | 60 | 69 | 22,5 | 61 | 39 | 151 | 80 | 100 | M27 | 67 | 147 | 3,07 |

Blueprint

