

Lifting Eye Starpoint RUD VRM



Product information

Design: Octagonal lifting eye.

For bolts with min. quality class 10.9

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

Код товара	Код	Diameter mm	WLL ton	Thread	WLL straight lift ton	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	N mm	T mm	Bec kg
421100010272	VRM	-	0,1	M6	-	9	7	20	23	16	28	17	13	37	11	9	28	0,06
421100030270	VRM	25	0,3	M8	1	11	9	25	25	21	30	21	16,3	47	14	12	35	0,1
421100040270	VRM	25	0,4	M10	1	11	9	25	25	21	30	21	16,3	47	14	12	35	0,1
421107500270	VRM	30	0,75	M12	2	13	10	30	30	24	34	25	19,8	56	17	14	42	0,18
421100150270	VRM	35	1,5	M16	4	15	13	35	36	30	40	29	23,6	65	21	19	49	0,32
421100230270	VRM	40	2,3	M20	6	17	16	40	41	37	50	35	29,3	76	23	24	58	0,48
421100320270	VRM	48	3,2	M24	8	20	19	49	51	45	60	41	35,2	92	29	30	70	0,83
421100450270	VRM	60	4,5	M30	12	26	24	60	66	56	75	51	44	114	36	36	87	1,32

Blueprint

